

FLOOR FRAME INSTALLATION



Please follow the instructions below to ensure long-term use and durability of the floor frames. Feel free to contact our label experts for further tips and advice.



Installation with the use of industrial polymer sealant

1. Clean the floor thoroughly with water and a scrub brush. Then, use a wet/dry vacuum cleaner to clean and dry the floor. Repeat this process until the water is clear. Use our industrial degreaser to remove any remaining grease or tyre tracks.
2. Degrease the frame with our industrial-strength degreasing spray.
3. Use an electric caulking gun to apply the polymer sealant to the back of the floor frame and make sure it's evenly spread out to a thickness of approximately Ø 3mm.
4. Do not apply the frame directly onto painted markings or lines, but along the markings instead to ensure proper adhesion.
5. Place the frame on the floor and use your fingertips to tap it softly until the sealant has been evenly spread out to a thickness of approximately Ø 1mm. Make sure the sealant doesn't spill out from under the edges.
6. Do not use or touch the newly installed frame for 24 hours, but preferably 48 hours, to enable the sealant to cure completely at room temperature.
7. Remove the liner, place the label in the centre of the frame and cover it with the transparent label cover, if applicable.



Installation with the use of concrete screws

1. Clean the floor thoroughly with water and a scrub brush. Then, use a wet/dry vacuum cleaner to clean and dry the floor. Repeat this process until the water is clear. Use our industrial degreaser to remove any remaining grease or tyre tracks.
2. Use an impact driver and drill four holes at a 90 degree angle straight into the ground. Make sure the holes are at least 20% deeper than the length of the screw.
3. Clear the dust and debris from the holes. Put the frame in place and screw it to the floor using the concrete screws and an impact wrench.
4. Remove the liner, place the label in the centre of the frame and cover it with the transparent label cover, if applicable.

Additional tips

- Make sure newly painted surfaces have had proper time to dry to prevent lingering fumes and gases from lifting the labels off the surface.
- The durability of the floor frames is dependent upon the type of floor, the condition of the floor, the amount of warehouse traffic and proper label application. Therefore, ONE2ID can't guarantee long-term adhesion. Please contact our label advisors for advice on the type of floor identification that best suits your work environment.